

FS-720 Specifications

BASIC SPECIFICATIONS:

Configuration:	Desktop Monochrome Printer with Standard 250 Sheet Drawer plus Single Sheet Multi-Purpose Tray
Resolution:	600 x 600 dpi
Printer Memory:	Standard / Max 8MB
Electrical Requirements:	120V, 60Hz, 6.8A
Dimensions:	15.0"W x 15.4"D x 9.6"H
Weight:	20.3 lbs
Max Duty Cycle:	12,000 Pages per month

CONTROLLER SPECIFICATIONS:

Controller:	32bit RISC
Supported PDL / Emulations:	Kyocera Mita Advanced Data Stream (KMADS)
Windows OS Compatibility:	Windows 98SE/Me/2000/XP
Connectivity / Interface:	Full-Speed USB 2.0
Driver:	Host Based

OUTPUT SPEEDS:

Warm-Up Time:	Less than 16 Seconds
First Print Out:	Less than 11 Seconds
Pages Per Minute:	17 Letter / 16 A4 / 15 Legal

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Drawer, Single Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 13", 8.5" x 14", A4, B5, A5
MPT Paper Size:	8.5" x 11", 8.5" x 13", 8.5" x 14", A4, B5, A5, Custom (2.8" x 5.8" - 8.5" x 14")
Paper Capacity:	251 Sheets
Paper Weight:	16-28 lb Bond via Paper Drawer, 16 lb Bond - 90 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

CONSUMABLES:

TK-112E:	2,000 pages @ 5% Coverage
----------	---------------------------

* Ships with 3,000 pages @ 5% Coverage. ISO/IEC 19752 Compliant.



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2005 Kyocera Mita America, Inc.
www.kyoceramita.com/us

